


ZC Height 5.5mmL, Low Impedance Series



- Chip type, low impedance temperature range up to 105°C
- Designed for surface mounting on high density PC board
- Applicable to automatic insertion machine using carrier tape
- Complied to the RoHS directive



Item	Characteristics					
Operating temperature range	-55 ~ +105°C					
Leakage current max.	I = 0.01CV or 3μA whichever is greater (after 2 minutes)					
Capacitance tolerance	±20% at 120Hz, 20°C					
Dissipation factor max. (at 120Hz, 20°C)	WV	6.3	10	16	25	35
	tanδ	0.22	0.19	0.16	0.14	0.12
Low temperature characteristics (Impedance ratio at 120Hz)	WV	6.3	10	16	25	35
	Z-25°C/Z+20°C	2	2	2	2	3
	Z-55°C/Z+20°C	4	4	3	3	3
Load life (after application of the rated voltage for 1000 hours at 105°C)	Leakage current	Less than specified value				
	Capacitance change	Within ±20% of initial value				
	tanδ	Less than 200% of specified value				
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and tanδ are same as load life value. The measurement shall be performed at 20°C by the KS C IEC 60384 - 4					
Resistance to soldering heat	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them at 250°C for 10 seconds.					
	Leakage current	Less than specified value				
	Capacitance change	Within ±10% of initial value				
	tanδ	Less than specified value				

● DRAWING (See page 69)

Unit : mm

-Series code of ZC is "Z"

CHIP TYPES

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF \ WV	6.3			10			16			25			35			
1.0														4×5.3	5.0	50
1.5														4×5.3	5.0	50
2.2														4×5.3	5.0	50
3.3														4×5.3	5.0	50
4.7														4×5.3	5.0	50
6.8											4×5.3	5.0	50	4×5.3	5.0	50
10											4×5.3	5.0	50	4×5.3	5.0	50
15											5×5.3	2.6	80	5×5.3	2.6	80
22											5×5.3	2.6	80	6.3×5.3	1.3	115
33											6.3×5.3	1.3	115	6.3×5.3	1.3	115
47											6.3×5.3	1.3	115	6.3×5.3	1.3	115
68											6.3×5.3	1.3	115	6.3×5.3	1.3	115
100											6.3×5.3	1.3	115	6.3×5.3	1.3	115

← Ripple current (mA rms) at 105°C, 100kHz
 ↑ Impedance (Ω) at 20°C, 100kHz
 Case size ØD×L(mm)

● FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz ≤
Coefficient	0.35	0.5	0.64	0.83	1.00